



IQ LOCK TOUCH-PGP

One solution for every application



Selectable protocol

Support PowerG+ and Z-Wave customers with a single lock solution. Reduce inventory costs, simplify truck stock and expand service opportunities.



Keyless convenience

Provide secure, keyless entry with a modern touchscreen interface that eliminates lost-key hassles and enhances end-user experience.



Compact design

The compact back unit fits doors with existing privacy locks to maximize installation flexibility. Ideal for MDU applications.



Over-the-air updates

Save time and operating costs by delivering firmware updates remotely, minimizing service visits.



Flexible deployment

Install as a standalone lock or as part of a connected security system to address more customer needs with a single solution.



Less maintenance

Long battery life reduces replacement frequency, minimizing maintenance visits while improving end-user satisfaction.



PowerG+

DSC

Johnson
Controls 

SPECIFICATIONS

Finish Options	Oil-Rubbed Bronze, Satin Nickel, Matte Black
Bolt Type	Motorized/Standard deadbolt
Backset	2.375 in./2.75 in. Adjustable (60/70 mm)
Door Prep	1.5 in./2.175 in. (38/54 mm)
Code Capacity	Network Mode: 250 x User codes Standalone Mode: 1 x Master User Code + 5 User Codes
Code Length	4-8 digits
Wireless Communication Protocol	Selectable PowerG + or Z-Wave Long Range
Power Supply	Four AA alkaline batteries
Lockout Mode	Keypad lockout for 3 minutes after 10 entries of invalid user code
Battery Life	PowerG + Mode: Minimum 14 months Z-Wave Mode: Minimum 12 Months Note: Based on ten unlocking and locking cycles for each day, including six cycles through smart lock keypad, and four cycles through network
IP Rating	Exterior assembly: IP54
Operating Temperature	Exterior assembly: -35°C to 66°C (-31°F to 151°F) Interior assembly: 0°C to 60°C (32°F to 140°F)
Storage Temperature	0°C to 49°C (32°F to 120°F)
Storage Humidity	20% to 60%
Operating Humidity	Exterior: 100% condensing Interior: 20% - 95% non-condensing
Weight (without batteries)	Exterior Assembly: 0.73 lb (0.33 kg) Interior Assembly: 1.0 lb (0.47 kg)
Certifications	FCC, IC, ANSI BHMA A156.36 Grade 2, UL10C (20min Fire Rating)

Product Details

SPECIFICATIONS	PART NUMBER	IMAGE
Matted Black	IQDLK-PGONKT-MB	
Satin Nickel	IQDLK-PGONKT-SN	
Oil-Rubbed Bronze	IQDLK-PGONKT-ORB	



PowerG+

DSC

